



A valmont  COMPANY

# Stainless Steel / Woven Wire

# Galvanised Woven Wire

R20 Aperture (mm)	Diameter (mm)	Mesh	Swg	Approx. % open space	Approx. weight kg/m2
25.00	3.15	1 1/8	10	79	4.5
22.40	3.15	1	10	77	4.9
19.00	2.50	7/8	12	78	3.7
11.20	1.60	2	16	77	2.5
10.00	2.50	2	12	64	6.4
10.00	2.0	2	14	69	4.2
7.10	1.60	3	16	67	3.7
7.10	1.25	3	18	72	2.4
6.30	2.0	3	14	58	6.1
6.30	1.25	3 1/2	18	69	2.6
5.60	0.90	4	20	74	1.6
5.00	1.60	4	16	57	4.9
5.00	1.25	4	18	64	3.2
4.00	1.25	5	18	58	3.8
3.55	1.60	5	16	48	6.3
3.15	1.25	6	18	51	4.5
3.15	0.90	6	20	60	2.5
2.50	0.71	8	22	61	2.0
2.24	0.90	8	20	51	3.3
2.00	1.25	8	18	38	6.1
2.00	0.90	9	20	48	3.6
2.00	0.56	10	24	61	1.6
2.00	0.45	10	26	67	1.1
1.80	0.71	10	22	51	2.6
1.60	0.90	10	20	41	4.1
1.60	0.56	12	24	55	1.9
1.60	0.45	12	26	61	1.3
1.40	0.71	12	22	44	3.0
1.40	0.45	14	26	56	1.4
1.25	0.56	14	24	47	2.2
1.25	0.36	16	28	61	1.0
1.12	0.45	16	26	51	1.6
1.00	0.56	16	24	41	2.6
0.90	0.36	20	28	51	1.3
0.85	0.56	18	24	36	2.8
0.80	0.45	20	26	41	2.1
0.71	0.32	24	30	48	1.2
0.63	0.45	24	26	35	2.4
0.56	0.28	30	32	44	1.2
0.50	0.32	30	30	38	1.5
0.40	0.22	40	34	41	1.0
0.32	0.18	50	36 1/2	40	0.8
0.25	0.16	60	37 1/2	37	0.8
0.24	0.14	70	38	38	0.7
0.18	0.13	80	39	38	0.7
0.16	0.10	100	42	38	0.5
0.13	0.080	120	44	37	0.4
0.10	0.071	150	45	34	0.4
0.10	0.045	180	47 1/2	45	0.2
0.06	0.040	250	48	37	0.2
0.05	0.038	300	48 1/2	38	0.2
0.04	0.031	350	49	34	0.17
0.04	0.028	400	49 1/2	29	0.2

R20 Aperture (mm)	Diameter (mm)	Mesh	Swg	Approx. % open space	Approx. weight kg/m2
22.40	3.15	1	10	77	4.9
18.00	2.00	3/4	14	81	2.5
16.00	3.15	3/4	10	70	6.6
12.50	3.15	5/8	10	64	8.1
11.20	1.60	2	16	77	2.5
10.00	2.50	2	12	64	6.4
10.00	2.00	2	14	69	4.2
7.10	1.60	3	16	67	3.7
6.30	2.00	3	14	58	6.1
5.00	1.60	4	16	57	4.9
5.00	1.25	4	18	64	3.2
4.00	1.25	5	18	58	3.8
3.15	1.25	6	18	51	4.5
2.24	0.90	8	20	51	3.3
2.00	0.90	9	20	48	3.6
1.25	0.90	12	20	34	4.8
1.60	0.56	12	24	55	1.9
1.25	0.36	16	28	61	1.0
0.90	0.36	20	28	51	1.3

1800 635 947 (Aus)  
www.locker.com.au

0800 285 837 (NZ)  
www.lockernz.co.nz